

System Configuration

Item	Description	Part Number
1	Power/control unit 230/460/575v	51-41-42
1B	Power/control unit 220/380/415/440v	51-42-11
2	NS 40 Welding Gun	751-585-500
3	15 ft. Ground Cable and Clamp (2)	720-070-002
4	25 ft. Combination Cable	722-000-058
Option	s	
	NS 40 Short Cycle Welding Gun	751-585-570
	Steel Tranquil-Arc® (NS 40 only)	512-241-000
	Aluminum Tranquil-Arc Kit (NS 40 only)	512-241-100

Recommended Settings-Drawn Arc

Stud Dia.	Weld Base Dia.	Time/Sec.	Current/Amps
3/16" (5mm)	0.187	0.15	300
1/4" (6mm)	0.250	0.17	425
5/16" (8mm)	0.312	0.25	500
3/8" (10mm)	0.375	0.33	550
1/2" (13mm)	0.500	0.55	800
5/8" (16mm)	0.625	0.67	1200

Duty Cycle

Rated at continu	uous operation
5/8" (16mm)	6 per minute
1/2" (13mm)	10 per minute
3/8" (10mm)	Unlimited

Features & Benefits

- Operates from 3 phase power for a smoother, more stable arc.
- Closed loop circuitry regulates power output to adjust for effects of cable heating and incoming power fluctuations.
- Infinitely adjustable time and current controls allow for precise weld adjustments.
- High duty cycle rating makes it an excellent choice for use with high speed automated equipment.
- By activating the "Short Cycle" feature unit can weld to thin gauge materials without the use of ferrules.
- Other important features include LED's, chuck saver circuit, thermal protection and cooling fan, and wheel set with and lifting eyes.

Specifications Power Control Unit

Timing Control

Regulated Output

Transformer Rating 2400 amps Stud Range 1/8"-5/8" (3

 Stud Range
 1/8"-5/8" (3mm-16mm)

 Input voltage
 230/460/575v, 50/60hz

 220/380/415/440v, 50/60hz

Fusing 100 amp @ 230v 60 amp @ 460v & 575v

.01 – 1.0 seconds, stepless 100 – 1400 amps stepless

Case Dim. 26-1/2" H x 20" W x 29" D (673mm x 508mm x 736mm)

Weight 475 lbs. (215kg)


Guns

Standard Duty Drawn Arc— NS 40, two wire, 751-585-500 Short Cycle—

NS 40 SC, two wire, 751-585-570

Gun Capacity Length Weight w/o cables

Weight w/working weight of cables



NS 40 SC 5/8" (16mm) 3/8" (10mm) 7-1/2" (190mm) 7-1/2" (190mm) 3 lbs. 1 oz.(1.4kg) 3 lbs. 8 oz.(1.6kg) 4 lbs. 10 oz.(2.1kg) 5 lbs. 4 oz.(2.4kg)